



Main Features

- OnBoard Intel® Atom™ D425 Processor, 1.8 GHz
- Intel® ICH8M chipsets
- Dual Intel® 10/100/1000 Mbps LAN Ports; Support WoL, teaming, PXE
- 4x USB2.0
- 1x RS232/422/485 and 3x RS232
- 1x Mini-PCIe with Two Antenna Holes and One SIM Card Holder
- 1x DB15 Digital Input & Output
- Support +12VDC Input; Support ATX power mode

Product Overview

Designed with Intel® D425 1.8 GHz processor and ICH8M embedded chipset and 12VDC input to take a low power consumption advantage, NISE 103 is a compact fanless industrial computing housed in a size of 185mm x 131mm x 54mm. The NISE 103 supports three RS232, one RS232/422/485, two 10/100/1000 LAN port, four USB ports, one digital I/O, one VGA display, audio jack (speaker-out, Mic-in) and one external CF card socket. It is also a wireless-ready platform which has Mini-PCIe socket and SIM card holder onBoard to support optional GSM wireless module or Wi-Fi module (default). EZ Controller, NISE 103 has a digital I/O port which offers 8X isolated digital input/output channels.

With isolation protection of 2,500VDC, and dry contact support, NISE103 can be applied to industrial and building automation applications. With rich IO connection in palm-sized system, NISE103 is an ideal fanless system for gate control, public information, self-service system, POS, Kiosk, low-power budget devices, and transportation applications etc.

Specifications

CPU Support

- OnBoard Intel® Atom™ D425 processor, 1.8 GHz
- Intel® ICH8M chipsets

Main Memory

- 1x DDR3 SO-DIMM sockets, single channel, support up to 2GB DDR3 667/800 SDRAM, un-buffered and non-ECC

I/O Interface-Front

- ATX power on/off switch
- HDD access/ power status LEDs
- 3x COM ports
COM2: RS232/422/485
COM3& COM4: RS232
- 2x USB2.0 port
- Audio jack (Line-out, Mic-in)
- 2x Antenna holes

I/O Interface-Rear

- 1x VGA
- COM1: 1x RS232
- 2x Intel® GbE LAN port; Support WoL, teaming and PXE
- 2x USB2.0 port

- +12VDC power input
- 1x DB15 male digital input & output


Digital Input & Output

- 4x Digital Input (Source type)
 - Input Voltage (Dry Contact):
Logic 0: Close to GND
Logic 1: Open
 - Input Voltage:
Logic 0: 3V max
Logic 1: +5V to +30V
- 4x Digital Output
 - Supply voltage: 5~30VDC
 - Sink current: 200 mA max. per channel

Device

- 1x 2.5" HDD driver bay
- 1x External CF Socket
- 1x SATA DOM
- 1x Mini-PCIe socket
Default: support optional Wi-Fi module
Option: support optional 3.5G module

Dimension Drawing



Power Requirements

- DC to DC power designed for onBoard support of +12VDC
- 1x optional 12V, 60W power adapter

Dimensions

- 185mm (W) x 131mm (D) x 54mm (H) (7.28" x 5.2" x 2.13")

Construction

- Aluminum chassis with fanless design

Environment

- Operating temperature:
 - Ambient with air flow: -5°C to 55°C
 - (According to IEC60068-2-1, IEC60068-2-2, IEC60068-2-14)
- Storage temperature: -20°C to 80°C
- Relative humidity: 10% to 93% (non-Condensing)
- Shock protection:
 - HDD: 20G, half sine, 11ms, IEC60068-2-27
 - CF: 50G, half sine, 11ms, IEC60068-2-27
- Vibration protection w/ HDD Condition
 - Random: 0.5Grms @ 5~500 Hz according to IEC60068-2-64
 - Sinusoidal: 0.5Grms @ 5~500 Hz according to IEC60068-2-6

Certifications

- CE approval
- FCC Class A

Ordering Information

Barebone

- **NISE 103 (P/N: 10J00010300X0)**
Intel® Atom™ D425 Fanless System
- **12V, 60W AC/ DC power adapter w/o power cord (P/N: 7400060013X00)**